

WIZ100SR/105SR/110SR Configuration Tool ver 3.0.2

Version

5.13

☒ Enable Serial Debug Mode

Not Connected

Board list

00:08:DC:14:4E:43

Network

Serial

Option

IP Configuration Method

☐ Static

☒ DHCP

☐ PPPoE

Local IP

192.168.2.15

Port

5000

Subnet

255.255.255.0

Gateway

192.168.2.1

PPPoE ID

Password

Server IP

192.168.2.4

Port

5000

Operation Mode

☒ Client

☐ Server

☐ Mixed

☐ Use UDP mode

☐ Use DNS

DNS Server IP

192.168.2.1

Domain Name

☐ Direct IP Search

Search

Setting

Upload

Ping

Firewall

Exit

WIZ100SR/105SR/110SR Configuration Tool ver 3.0.2

Version

5.13

☒ Enable Serial Debug Mode

Not Connected

Board list

00:08:DC:14:4E:43

Network

Serial

Option

Speed

230400

DataBit

8

Parity

None

Stop Bit

1

Flow

CTS/RTS

☐ Direct IP Search

Search

Setting

Upload

Ping

Firewall

Exit

WIZ100SR/105SR/110SR Configuration Tool ver 3.0.2

Version5.13

☒ Enable Serial Debug Mode

Not Connected

Board list

00:08:DC:14:4E:43

NetworkSerialOption

Inactivity time0(0 ~ 65535 sec)

* Closes socket connection, if there is no transmission during this time.

Data Packing Condition

Time0(0 ~ 65535 ms)

Size0(0 ~ 255 Byte)

Char00(Hexacode)

Password (TCP Server)

☐ Enable

Password(Max 8 Bytes)

Serial Configuration

☒ Enable

Code2B2B2B(in Hex)

☐ Direct IP Search

Search

Setting

Upload

Ping

Firewall

Exit